

Progress Report on NASA Grant: NGR 11-002-096

RESEARCH ON THE ELASTIC STABILITY

of  
LARGE SHELLS



Principal Investigator: Professor Wilfred H. Horton

(NASA-CR-139665) RESEARCH ON THE ELASTIC  
STABILITY OF LARGE SHELLS Semianual  
Progress Report (Georgia Inst. of Tech.)  
18 p HC \$4.00

N74-33360

CSCL 20K

Unclass

G3/32 47899

Considerable progress has been made on the large shell tests. The remaining three shells have all been completely instrumented, checked for circularity and surveyed for stiffness. One shell has been installed in the test facility and a series of preliminary load distribution checks have been made. These tests have indicated that we can now achieve a better distribution of stress in the central bays than in the prior tests. In fact at low load levels the stresses in the center bay were uniform around the shell to within  $\pm 2.5\%$ , and this degree of uniformity improves with increasing load. The degree of uniformity in the bays at either end of the shell was not of this degree of excellence although it was good in comparison with that normally accomplished. The difficulty experienced in smoothing this distribution and avoiding local bending actions in the lower regions is the lack of mating between the end surface of the shell and the loading device. We have made substantial progress in evaluating this discrepancy. For this purpose we have adopted plastigages, (perfect circle plastigage Type PG I clearance range .001 to .003 inch) made by Perfect Circle Hagerstown, Indiana. These devices are thin plastic rods which are inserted between the two surfaces whose degree of mating is in question. When the two surfaces are mated together the plastic gages are flattened by amounts which are related to the degree of fit. We have used some 250 measuring stations around the ends of the shell and from the flattening actions have been able to quantify the discrepancies. These discrepancies in fit are readily correlatable with the strain distributions measured. The shell is now being reworked to remove the high and low spots. Maximum discrepancy achieved in the preliminary end matching was of the order  $\pm 2$  thousandths, but the majority of the surface was much closer than this. We have removed the vehicle from the test frame

and are now in the process of reducing this discrepancy. We are confident that we can achieve a tolerance of  $\pm 1$  thousandth, and with patience possible do somewhat better.

The stiffness surveys are most informative. We can readily detect the various frame joints and steps are being taken to modify the frame joints in such a manner as to produce a stronger joint which at the same time does not produce as substantial a local stiffness variation as is currently experienced. An analysis of the first shell test results leads us to the opinion that the instability load level in that test was marked, influenced by the ring behavior in the neighborhood of a lap joint. We feel certain that the changes which we have in mind will improve the shell performance.

The very detailed studies of initial shape which we have made give clear indication that the shell initial geometry is excellent. In the circumferential direction, for the vehicle now being readied for test, there is a dominant double wave and a six wave component which may well be due to the construction from six panels. The amplitudes are small however.

In the longitudinal direction the wave components higher than two contribute little to the deviation. In particular the wave components that might be associated with the presence of eight frames are not of any appreciable magnitude. However, some of the longitudinal generators are much straighter than others.


The various sheets attached to this report give quantitative description of the remarks made heretofore.

Figure 1 portrays the distribution of strain achieved in the central and end regions, while Figure 2 shows the variation along vertical generators chosen at random. In Table I we present an analysis of the circumferential deviation data and in Table II a similar analysis for the longitudinal information. The graphs of Figure 3 show the variation in stiffness around the frames of the shell and Figure 4 gives the mean stiffness distribution along the shell.

Stiffness contour maps and deviation contour maps are in the course of preparation but are not included here.

Some changes in the basic testing method have been made. The 72 hydraulic jacks which were used in prior work have been replaced by 18 larger jacks and the multiplicity of ground steel plates which were used between the jack ends and the base of the shell have been replaced by one heavy ring. These changes were made to (1) ease the many alignment problems (2) to improve the lower end load distribution. There is little doubt that these objectives have been met, but the attainment of a flat contact surface on this ring presented considerable difficulties since no local contractor could be found to fabricate the ring to our exacting requirement.

There seems, from tests which we have conducted, little doubt that the effects of the small discrepancies between the machined ends of the shells and the upper and lower end loading rings could readily be mitigated by the use of Devcon A, Plastic Steel. (Devcon Corporation, Danvers, Massachusetts, 01923). However, it is our considered opinion that its use would involve more work than is entailed in the adjustment process which we are adopting, since the two end rings would require special surfacing for each test. The surfacing of these rings is a long and tedious process since no machine shop in the area has appropriate tools.



**FIGURE 1D**  
**STRAIN DISTRIBUTION ALONG**

**SHELL CIRCUMFERENCE -**  
**NASA S 3/20/74 TEST #1**

**REPRODUCTION OF THE**  
**ORIGINAL PAGE IS POOR**

**Bx X A**

**130°**

**230°**

**120°**

**240°**

**110°**

**250°**

**100°**

**260°**

**90°**

**270°**

**80°**

**280°**

**70°**

**290°**

**60°**

**300°**

**50°**

**310°**

**40°**

**320°**

**30°**

**330°**

**20°**

**340°**

**0**  
**10°**  
**20°**  
**30°**  
**40°**  
**50°**  
**60°**  
**70°**  
**80°**  
**90°**  
**100°**  
**110°**  
**120°**  
**130°**  
**140°**  
**150°**  
**160°**  
**170°**  
**180°**  
**190°**  
**200°**  
**210°**  
**220°**  
**230°**  
**240°**  
**250°**  
**260°**  
**270°**  
**280°**  
**290°**  
**300°**  
**310°**  
**320°**  
**330°**  
**340°**  
**350°**  
**360°**

**STRAINS IN INCHES/INCH**

**LEGEND:**

**○ - STRAIN AT OUTER SURFACE OF SKIN**  
**-△ - STRAIN AT INNER LIP OF STRANGER**  
**X - BAD DATA CHANNEL**

**NOTE:**

**SCALE HAS BEEN EXPANDED TO HIGHLIGHT**  
**DEVIATIONS FROM UNIFORMITY**

210°

150°

200°

140°

190°

120°

180°

0°

170°

190°

160°

200°

150°

210°

140°

220°

130°

230°

120°

240°

110°

250°

100°

260°

90°

270°

80°

280°

70°

290°

60°

300°

50°

310°

40°

320°

30°

330°

30°

340°

20°

350°

10°

0°

350°

10°

20°

340°

30°

330°

30°

340°

20°

350°

10°

0°

350°

10°

20°

340°

30°

330°

30°

340°

20°

350°

10°

0°

350°

10°

20°

340°

30°

330°

30°

340°

20°

350°

10°

0°

350°

10°

20°

340°

30°

330°

30°

340°

20°

350°

10°

0°

350°

10°

20°

340°

30°

330°

30°

340°

20°

350°

10°

0°

# FIGURE 1C

STRAIN DISTRIBUTION ALONG  
SHELL CIRCUMFERENCE  
NASA 5 - 8/26/74 #1

BAY 7  
REPRODUCIBILITY OF THE  
ORIGINAL PAGE IS POOR

STRAIN  
MICRO INCHES/INCH

## LEGEND

- STRAIN AT OUTER SURFACE OF SKIN
- △- STRAIN AT INNER LIP OF STRINGER
- ✗ BAD DATA CHANNEL

## NOTE:

SCALE HAS BEEN EXPANDED TO HIGHLIGHT  
DEVIATIONS FROM UNIFORMITY

REPRODUCIBILITY OF THE  
ORIGINAL PAGE IS POOR

LONGITUDINAL STRAND DISTRIBUTION  
ALONG 3 GENERATORS CHOSEN AT RANDOM

NASA 15 8/20/23

FIGURE 2a  
OUTSIDE (OKIN SURFACE)





FIGURE 2b  
INSIDE (LIP OF STRINGER)




LEGEND

- △ CIRCUMFERENTIAL STATION 6 (12° FROM DATUM)
- CIRCUMFERENTIAL STATION 11 (22° FROM DATUM)
- CIRCUMFERENTIAL STATION 17 (34° FROM DATUM)


NOTE: THE LONGITUDINAL STATIONS ARE THE CENTERS  
OF THE 8 EQUAL LENGTH BAYS.


NASA SHELL 5 VARIATION IN STIFFNESS AROUND RINGS 1, 2, 3, 4



REPRODUCIBILITY OF THE  
ORIGINAL PAGE IS POOR

FIGURE 3a (CONT'D)  
NASA SHELL 5 VARIATION IN STIFFNESS AROUND RINGS 1, 2, 3, 4









FIGURE 4 - MEAN STIFFNESS DISTRIBUTION  
ALONG SHELL - NASA E



REPRODUCIBILITY OF THE  
ORIGINAL PAGE IS POOR

Table I

FOURIER SERIES COEFFICIENTS FOR DEVIATION DATA (CIRCUMFERENTIAL)

BAY = 1 POSITION = 4

| # OF WAVES | AMPLITUDE (MILS) |
|------------|------------------|
| 0          | -30.5            |
| 1          | 4.4              |
| 2          | 55.9             |
| 3          | 5.8              |
| 4          | 1.9              |
| 5          | 2.5              |
| 6          | 6.4              |
| 7          | .8               |
| 8          | 1.8              |
| 9          | 1.5              |
| 10         | 1.7              |

BAY = 2 POSITION = 17.5

| # OF WAVES | AMPLITUDE (MILS) |
|------------|------------------|
| 0          | -23.9            |
| 1          | .9               |
| 2          | 56.6             |
| 3          | 9.5              |
| 4          | .9               |
| 5          | 3.2              |
| 6          | 11.9             |
| 7          | 2.1              |
| 8          | 3                |
| 9          | 4.6              |
| 10         | 2.5              |

BAY = 3 POSITION = 31

| # OF WAVES | AMPLITUDE (MILS) |
|------------|------------------|
| 0          | -11.6            |
| 1          | 2.7              |
| 2          | 56.1             |
| 3          | 12.1             |
| 4          | 3.8              |
| 5          | 3.8              |
| 6          | 11.1             |
| 7          | 1.5              |
| 8          | 2.4              |
| 9          | 4.7              |
| 10         | 3.8              |

BAY = 4 POSITION = 38.5

| # OF WAVES | AMPLITUDE (MILS) |
|------------|------------------|
| 0          | -8.6             |
| 1          | 3.6              |
| 2          | 56               |
| 3          | 13.2             |
| 4          | 4.6              |
| 5          | 3.5              |
| 6          | 10.1             |
| 7          | 1.7              |
| 8          | 2.4              |
| 9          | 3.2              |
| 10         | 2.8              |

Table I Continued

BAY = 4 POSITION = 44.5

| # OF WAVES | AMPLITUDE (MILS) |
|------------|------------------|
| 0          | -6.4             |
| 1          | 4.1              |
| 2          | 56.5             |
| 3          | 13.9             |
| 4          | 5.2              |
| 5          | 3                |
| 6          | 10.2             |
| 7          | 2.1              |
| 8          | 2.3              |
| 9          | 1.5              |
| 10         | 1.7              |

BAY = 4 POSITION = 58.5

| # OF WAVES | AMPLITUDE (MILS) |
|------------|------------------|
| 0          | .6               |
| 1          | 4                |
| 2          | 57               |
| 3          | 14.9             |
| 4          | 5.6              |
| 5          | 3                |
| 6          | 10.2             |
| 7          | 2.5              |
| 8          | 2.8              |
| 9          | 1                |
| 10         | 2.3              |

BAY = 5 POSITION = 58

| # OF WAVES | AMPLITUDE (MILS) |
|------------|------------------|
| 0          | 5.1              |
| 1          | 4.3              |
| 2          | 56.8             |
| 3          | 15.9             |
| 4          | 6.3              |
| 5          | 2.8              |
| 6          | 11               |
| 7          | 2.8              |
| 8          | 3                |
| 9          | 1.8              |
| 10         | 4.5              |

BAY = 6 POSITION = 71.5

| # OF WAVES | AMPLITUDE (MILS) |
|------------|------------------|
| 0          | 17.7             |
| 1          | 2.9              |
| 2          | 56.8             |
| 3          | 17.6             |
| 4          | 6.9              |
| 5          | 2.2              |
| 6          | 14.6             |
| 7          | 2.7              |
| 8          | 2                |
| 9          | 2.3              |
| 10         | 5                |

REPRODUCIBILITY OF THE  
ORIGINAL PAGE IS POOR

Table I Continued

BAY = 7 POSITION = 85

| # OF WAVES | AMPLITUDE (MILS) |
|------------|------------------|
| 0          | 22.5             |
| 1          | 1.3              |
| 2          | 56.6             |
| 3          | 17.1             |
| 4          | 5.8              |
| 5          | .6               |
| 6          | 12.2             |
| 7          | 2.7              |
| 8          | 1.6              |
| 9          | 1.4              |
| 10         | 2.2              |

BAY = 8 POSITION = 97

| # OF WAVES | AMPLITUDE (MILS) |
|------------|------------------|
| 0          | 15.7             |
| 1          | 5                |
| 2          | 56.1             |
| 3          | 15.9             |
| 4          | 3                |
| 5          | 1.2              |
| 6          | 6.9              |
| 7          | 1.1              |
| 8          | 1.6              |
| 9          | .7               |
| 10         | .7               |

Table II

## FOURIER SERIES COEFFICIENTS FOR DEVIATION DATA (LONGITUDINAL)

## 9 DEGREES

| # OF WAVES | AMPLITUDE |
|------------|-----------|
| 0          | 19.5      |
| 1          | 23.1      |
| 2          | 11        |
| 3          | 7         |
| 4          | 4.9       |
| 5          | 3.8       |
| 6          | 3.5       |
| 7          | 3.8       |
| 8          | 3.3       |
| 9          | 2.8       |
| 10         | 2.5       |

## 53 DEGREES

| # OF WAVES | AMPLITUDE |
|------------|-----------|
| 0          | -18.5     |
| 1          | 42        |
| 2          | 16.3      |
| 3          | 12        |
| 4          | 6.9       |
| 5          | 5.6       |
| 6          | 5.1       |
| 7          | 4.8       |
| 8          | 4.3       |
| 9          | 3.5       |
| 10         | 3.3       |

## 99 DEGREES

| # OF WAVES | AMPLITUDE |
|------------|-----------|
| 0          | -38.9     |
| 1          | 15.8      |
| 2          | 10.8      |
| 3          | 4.9       |
| 4          | 2.5       |
| 5          | 2.2       |
| 6          | 2.1       |
| 7          | 2.7       |
| 8          | 2.4       |
| 9          | 1.5       |
| 10         | 1.6       |

## 143 DEGREES

| # OF WAVES | AMPLITUDE |
|------------|-----------|
| 0          | 32        |
| 1          | 8.1       |
| 2          | 6.9       |
| 3          | 3.7       |
| 4          | 1.9       |
| 5          | 1.2       |
| 6          | .9        |
| 7          | 2.1       |
| 8          | 1.7       |
| 9          | .9        |
| 10         | 1.2       |

REPRODUCIBILITY OF THE  
ORIGINAL PAGE IS POOR

Table II Continued

189 DEGREES

| # OF WAVES | AMPLITUDE |
|------------|-----------|
| 0          | 44.7      |
| 1          | 33.2      |
| 2          | 14.3      |
| 3          | 8.3       |
| 4          | 5.2       |
| 5          | 4.7       |
| 6          | 4.2       |
| 7          | 4         |
| 8          | 3.5       |
| 9          | 2.9       |
| 10         | 2.9       |

233 DEGREES

| # OF WAVES | AMPLITUDE |
|------------|-----------|
| 0          | -38.5     |
| 1          | 32.6      |
| 2          | 15.3      |
| 3          | 10.5      |
| 4          | 6         |
| 5          | 4.8       |
| 6          | 4.4       |
| 7          | 4.5       |
| 8          | 4.1       |
| 9          | 3.4       |
| 10         | 3.3       |

279 DEGREES

| # OF WAVES | AMPLITUDE |
|------------|-----------|
| 0          | -40.6     |
| 1          | 10.8      |
| 2          | 6.9       |
| 3          | 3.2       |
| 4          | 2.1       |
| 5          | 2.1       |
| 6          | 1.7       |
| 7          | 2.2       |
| 8          | 2.3       |
| 9          | 1.3       |
| 10         | 1.6       |

323 DEGREES

| # OF WAVES | AMPLITUDE |
|------------|-----------|
| 0          | 51.2      |
| 1          | 28.9      |
| 2          | 9.8       |
| 3          | 3.9       |
| 4          | 3.4       |
| 5          | 2.8       |
| 6          | 2.6       |
| 7          | 2.6       |
| 8          | 2.6       |
| 9          | 2.1       |
| 10         | 2.1       |